

SOLUTIONS BY



MISSION CRITICAL FACILITIES
DESIGN AND CONSTRUCTION

Covis Sdn Bhd

E-03-01, 1st Floor East Wing
Subang Square Business Centre
Jalan SS15/4G, 47500,
Subang Jaya, Selangor

@ www.covis-group.com/
lawrence.lai@covis-group.com

+603 5621 7780

+603 5621 7790



• 1 Year Warranty •



Data/ Signal Line Protection

CVS Closed Circuit TV Protection

Features

- Automatic Recovery
- Low insertion Loss
- Easily Installed, Shielded Case and Miniature Size
- Designed for lightning protection on closed circuit TV systems
- Offers low loss even at frequencies approaching 500 Mhz.
- Comes with one year warranty include labour and parts

General Technical Specifications

Operating Voltage	5 VDC
Clamping Voltage	90 VDC (Spark Over Voltage)
Operating Current	0.15A
Peak Surge Current	10kA (8x20µS)
Frequency Range	0 to 1 GHz
Insertion Loss	<0.5 dB at 500Mhz <1.0 dB at 900Mhz
SPD Technology	Gas Discharge Tube (GDT)
Connection Type	BNC, 75 Ohm
Operating Temperature	-40°C to +85°C
Dimension (Inches)	0.6H x 0.6W x 2.0L
Weight	1 Oz
Certifications	ISO 9001: 2000

*Specification subjects to change without prior notice